CLIPPEDIMAGE= JP407207551A

PAT-NO: JP407207551A

DOCUMENT-IDENTIFIER: JP 07207551 A

TITLE: PRODUCTION OF KNITTED FABRIC HAVING HIGH ELASTIC PROPERTY

PUBN-DATE: August 8, 1995

INVENTOR-INFORMATION:
NAME
NISHIJIMA, SEIICHI
TAKAMI, MINORU
FUJIMOTO, YASUHIRO

ASSIGNEE-INFORMATION: NAME UNITIKA LTD

COUNTRY N/A

APPL-NO: JP05352138

APPL-DATE: December 31, 1993

INT-CL (IPC): D04B001/16; D06C007/00 ; D01F006/62 ; D01F006/62

ABSTRACT:

PURPOSE: To obtain a high-density knitted fabric having soft touch feeling of surface and excellent stretchability.

CONSTITUTION: Yarn A composed of thermally extensible polyester-based fiber is prepared. The thermally extensible polyester-based fiber is preferably produced by thermally stretching highly oriented undrawn yarn of polyester which has a main repeating unit composed of ethylene terephthalate and 15-45% structure integration parameter at a temperature ≥25°C higher than the glass transition temperature and heat-treating at a temperature 25-90°C lower than the melting point. Besides, yarn B comprising

thermally shrinkable polyester fiber is prepared. Knitting is carried out in such a way that the yarn A is positioned at the outside of knitted stitches by plaiting knitting and the yarn B is arranged inside the knitted stitches. The knitted fabric is dyed, processed and heat-treated during the dyeing and processing.

COPYRIGHT: (C)1995, JPO